

# Touchscreen Stand



## Key features

- ▼ Integrated touchscreen monitor and small PC for simple, convenient screening operation



All-in-one support solution for fixed deployment of Thruvision cameras

- ▼ Operator adjustable monitor mounting arm for comfort and convenience
- ▼ Integrated cable management for safe and tidy deployment
- ▼ Single mains connection for speed and ease of deployment
- ▼ Sturdy base for safe operation



Integrated 24" touchscreen display

For fixed deployment of Thruvision's proven people-screening cameras



TV-MNT-FIX-TOUCH with Thruvision LPC8 camera installed

## Technical Specifications

Camera Compatibility	
Compatible with:	Thruvision LPC (TV-LPC4/8/16) Thruvision TAC (TV-TAC8/16)
Compute	
Processor:	8th Gen Intel Core i7
RAM:	8.0 GB DDR4 SDRAM
Storage:	256 GB SATA SSD
Graphics:	Intel UHD Graphics 630
Operating System:	Microsoft Windows 10 Professional 64-bit
Display	
Screen diagonal:	60.5 cm (23.8 in)
Screen type:	16:9 touchscreen
Screen resolution:	1,920 x 1,080 px
Electrical	
Operating voltage:	Rated range 100 to 240 V a.c., 50 to 60 Hz
Power consumption:	Less than 225 W
Physical	
Dimensions (h x l x w) with camera installed:	1,535 x 660 x 620 mm (60.4 x 26.0 x 24.4 in)
Weight:	37.4 kg (82.4 lb) 63.4 kg (139.6 lb) with camera
Colour:	Black
Environmental	
Ambient environment:	Indoors, dry and preferably air-conditioned location
Operating temperature:	5 to 35 °C (41 to 95 °F)
Relative humidity:	20 to 85% RH, non-condensing
Storage temperature:	0 to 55 °C (32 to 131 °F)

**NOTE:**

- Hardware specifications are subject to frequent change by manufacturers, and are provided as a guide only.
- Specifications of supplied hardware may therefore differ from those stated above.
- Thruvision will use best endeavours to supply hardware that meets or exceeds the stated specifications.

**PART NUMBER: TV-MNT-FIX-TOUCH**

**THRUVISION**

info@thruvision.com  
thruvision.com

UK t: +44 (0) 1235 425400  
US t: +1 (540) 878-4844

Follow us on 